



ORCHARD INDUSTRY IMPLEMENTS

SPRAYERS AND SLASHERS FOR PRODUCTIVITY AND EFFICIENCY



TIFONE

LARGE CAPACITY,
VERY ROBUST
SPRAYER

TIFONE - WHEN HIGH QUALITY TAKES TO THE FIELD

The Tifone Vector is a line of very robust sprayers with large capacity tanks that withstands all types of stress. Equipped with a unique design, compact double frame with hemispheric bow offering maximum functionality.

An infinite series of axial and radial propeller fan devices can be applied. It is equipped with a graduated mechanical level and circuit flushing system incorporated into the frame to help limit the size without losing capacity in the main tank.

Available with axial or turbine fans to meet all types of crop treatments and suitable for the spraying of Tree Plantations such as Macadamia and Avocados. Other usages include: Citrus, Bananas, Chestnuts, Cherries, Almonds, Walnuts, Hazelnuts, Olives, Pears, Peaches and Plums for Row crops in open field and in Greenhouses. Available in a 2,000L, 3,000L and 4,000L capacities.

SPRAY TREE
COVER
25M HIGH



- HD Polyethylene tank with innovative front pickup and excellent agitation.
- Double radial structure frame with hemispheric bow, protective band on the ground for the tank, for operating on rough, muddy terrain. Includes a fresh water tank.
- "Telecontrol Exact" stable pressure regulator.
- Spring suspension on axle.
- Circuit flushing system incorporated into the frame with selection with special valve.
- Autofilter: the self-cleaning filter automatically continuously flushes.
- Suction probe F2 for instant dosing of pesticide/fungicide in total safety.
- Suitable for Powders, Granules and Liquids.
- Commands are located on the left side to ensure maximum safety for operator Pesticides container with safety lock.
- Hand washing tank.
- Circuit Flushing Tank with instant selecting valve (part of frame).
- Hydraulically adjustable on each canon set.
- Axle and drawbar height and length/width adjustability.
- Large mechanical tank content meter.

MODELS

SPECIFICATIONS

100% ITALIAN MADE

Vector Big 4000



Vector Big 3000



Storm 2000



	VECTOR BIG 4000	VECTOR BIG 3000	STORM 2000
Tank Capacity	4000L	3000L	2250L
Rinse Tank Capacity	55L	55L	80L
Handwash Tank Capacity	16L	16L	16L
Integral Agitation	Dual-Mixer	Dual-Mixer	Turbo Mixer / Geysers
Pump	TEA 110 / 150	TEA 110 / 150	TEA 110 / 150
Telecontrol	Autofilter	Autofilter	Autofilter
Chemical Suction Probe	F2	F2	F2
Tyres	400 / 500	400 / 500	11.5 / 80
Dimensions	410 x 170 x 175	335 x 170 x 175	
Empty Weight	1,440kg	1,170kg	



ADVANCED SPRAYING EQUIPMENT

PERFECT MOWERS

SOLO-SWING (ATTACHMENT) - SZA SERIES



The Solo-Swing is a swinging arm, driven by a hydraulic motor. It's simple but robust construction allows to automatically mow around trees and fence posts.

The SZA is an attachment model which can be supplied with mounting brackets to be fitted to a slasher or mulcher.

Mechanic-hydraulic feeler

For young trees, lighter posts or when operating on inclines all Perfect Solo-Swing mowers can be provided with a hydraulic feeler mechanism.

Swing Away Blades

All Solo-Swing models have swing-away blades, which are less vulnerable to obstacles. These blades come standard.

SOLO-SWING (FRONT MOUNT) - SZL SERIES

The standard configuration of the SZL models is a tractor front mount version with hydraulic offset and two support wheels. The cutting width is 60cm.

The Solo-Swing comes automatically in transport position as soon as the swing arm is being retracted properly.

The 3-point front linkage is not necessary for use of the SZL models.



SPECIFICATIONS

	SZA-600	SZA-850	SZL-600
Cutting Width	60cm (2'0")	85cm (2'9.5")	60cm (2'0")
Oil Flow Requirements	30L/min	30L/min	30L/min
Oil Pressure Requirements	+80bar / 1160psi	+80bar / 1160psi	+80bar / 1160psi
Displacement of Motor	16cc / 1cu.in.	17,9cc / 1,1cu.in.	16cc / 1cu.in.
Cutting Angle	0-15°	0-15°	0-15°
Discharge Angle	0-15°	0-15°	0-15°
Tractor Hydraulics Required	1 x double acting valve 1x free flow return	1 x double acting valve 1x free flow return	2 x double acting valve 1x free flow return
Offset from Tractor Centre	-	-	210cm (6'11")
Weight	95kg (210lbs)	110kg (242lbs)	200kg (440lbs)



VAN WAMEL BV

PERFECT MOWERS

SINGLE BRUSH SWEEPER - SPA SERIES

Perfect Mowers brush sweepers are designed to remove the nuts, pruning's and leaf residues which are in the tree or vine rows and to clean the herbicide strips in order to discourage the development of fungus and to implement chemical weed control.

They are driven by a hydraulic motor and are equipped with elastic and highly resistant sweeper brushes which spin at approximately 150rpm.

The sweeper head position is adjustable both in working angle and in working height, which assures a high-quality working result in all conditions.

For perfect terrain adjustment the sweeper head is supported by a swivel wheel. In transport position the brush sweeper can be lifted manually or by means of a hydraulic ram.

These models can be fitted to implements, such as slashers and mulchers.



DOUBLE BRUSH SWEEPER - SPD SERIES

A double brush sweeper clears the two tree rows in one pass from nuts, leaves and pruning's. The working width is adjustable up to 400cm.

The SPDA sweeper is especially designed for use in the tractor 3-point linkage.

The double front mounted brush sweeper (SPDF) is equipped with a carriage beam for mounting to the front of the tractor and the standard configuration the machine is equipped with hydraulic rams to adjust the working width and to lift the sweepers.

These models can be fitted to implements, such as slashers and mulchers.

SPECIFICATIONS

SINGLE BRUSH SWEEPER	SPA	SPF
Sweeper Width	100cm (3'3")	100cm (3'3")
Oil Flow Requirements	30L/min	30L/min
Oil Pressure Requirements	+70bar / 1015psi	+70bar / 1015psi
Tractor Hydraulics Required	1 x double acting, 1 x single acting, 1x free flow return	1 x double acting, 1 x single acting, 1x free flow return

DOUBLE BRUSH SWEEPER	SPDA	SPDF
Sweeper Width	2 x 100cm (3'3")	2 x 100cm (3'3")
Oil Flow Requirements	30L/min	30L/min
Oil Pressure Requirements	+70bar / 1015psi	+70bar / 1015psi
Tractor Hydraulics Required	1 x double acting, 1 x single acting, 1x free flow return	1 x double acting, 1 x single acting, 1x free flow return

**IT WAS GREAT THEN, AND BECAUSE
OF YOU, IT'S EVEN BETTER TODAY!**

**“GREAT FARMERS
DESERVE GREAT
MACHINERY”**

DSO10.50

Shown with standard
chain shielding





SINGLE SPINDLE

4ft - 7ft cut

BB840XDW

The Woods Equipment BB840XDW Brushbull Single Spindle slasher is a medium duty single spindle slasher. It has a 2.1m (7') cut and has a 75mm cutting capacity. The gearbox horsepower is 120hp.

- Does not leave a windrow
- Change blades from above the slasher
- Quick Change blade pins
- Built on a complete subframe
- Stump Jumping disc standard
- Built in USA with American steel
- Five year warranty gear box, three year rust through warranty on deck
- Optional side throw ability



BATWING

12ft - 20ft cut

BW15.50

The BW15.50W is the new **Customer Designed** Batwing which has new redesigned features to make it more reliable, more durable, easier-to-use, easier-to-maintain and built to perform better.

The standard duty 15ft Batwing slasher can cut material up to 65mm in size. The standard duty 15ft Batwing slasher suits tractors ranging between 45hp and 200hp. The cutting capacity is 4.57m (15ft). Wing operating range is 90 degrees up and 22 degrees down.

**SAFEST & MOST RUGGED
SLASHERS ON THE MARKET**

IT WAS GREAT THEN, AND BECAUSE OF YOU, IT'S EVEN BETTER TODAY!



MULTI SPINDLE

8ft - 16ft cut

MDS8.50 / 10.50

The Woods Equipment MDS8.50W / 10.50W Multi Spindle slasher is a heavy-duty dual spindle slasher. It has a 2.4m - 3m (8'-10') cut and has a 75mm diameter cutting capacity. The gearbox is 205hp (splitter) 160hp (spindles). This model is a 3-point linkage attachment.

- Does not leave a windrow
- Change blades from above the slasher
- Quick Change blade pins
- Built on a complete subframe
- Stump Jumping disc standard
- Built in USA with American steel
- Six-year gear box warranty, three-year rust through warranty on deck
- Optional side throw ability



MULTI SPINDLE

8ft - 16ft cut

DSO10.50

The Woods Equipment DSO10.50W Multi Spindle offset slasher is a heavy-duty dual spindle slasher. This is a hydraulic offset model. It has a 3m (10') cut and has a 75mm diameter cutting capacity. The gearbox is 205hp (splitter) 160hp (spindles). This model is a drawbar attachment.

- Does not leave a windrow
- Change blades from above the slasher
- Quick Change blade pins
- Built on a complete subframe
- Stump Jumping disc standard
- Hydraulic offset - 685mm right, 125mm left
- Six-year gear box warranty, three-year rust through warranty on deck
- Optional side throw ability



FINISHING MOWERS

4ft - 7ft cut

PRD8400

The Woods Equipment PRD8400 Finishing Mower is a medium-duty mower with a 2.1m (84") cutting width and a 60hp gearbox, designed and manufactured for harsher usage and tougher applications.

- Three-point: Cat 1
- Ideal for mowing lawns, sports fields and parks
- Features a strong, eight gauge steel deck and a powerful 60hp gearbox
- Belt with clutching cover protects parts and increases lifespan
- Anti-shimmy caster wheel springs reduce shock load - tubular caster wheel arms add strength



GRADER BLADE

5ft - 10ft

RB96.60

The Woods Equipment RB96.60 Rear Blade is designed for grading dirt or driveways, cleaning up construction sites or moving snow - rely on Woods durable rear blades for maximum performance.

- Optional rear wheel available.
- Double-bevelled, reversible and hardened cutting edge for long life
- Chose manual or hydraulic, featuring angle, offset and tilt adjustments

**SAFEST & MOST RUGGED
SLASHERS ON THE MARKET**



**1137 Nambour Connection Rd,
Parklands, Qld Australia 4560**

(07) 5441 5677

**info@tisca.com.au
tisca.com.au**

